## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Issue date: 27/09/2023 Version: 1.0



# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixture

Product name : Arc Brush Cleaner : D800-U0RP-00W-1RW8 UFI

Product code : TEBC001 Product group : End product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Use of the substance/mixture : Paint brush cleaner

1.2.2. Uses advised against

Restrictions on use : Cosmetics, personal care products

## 1.3. Details of the supplier of the safety data sheet

#### Supplier

Arc Building ProductsÁ

IDA Business & Technology Park

Ballynattin

Arklow

Co. WicklowÁ

Ireland

+353 (0)402 32370Á

sales@arcbuildingproducts.ie

### 1.4. Emergency telephone number

**Emergency number** : +353 (0)402 32370

(Office hours only)

NHS 111 - General Public (24 Hour service)

Country	Organisation/Company	Address	Emergency number
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)

Also, in the event of a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department.

### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226 Specific target organ toxicity - Single exposure, Category 3, Narcosis H336 Specific target organ toxicity - Repeated exposure, Category 1 H372 H304 Aspiration hazard, Category 1 Hazardous to the aquatic environment - Chronic Hazard, Category 2 H411

Full text of H- and EUH-statements: see section 16

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878



#### Adverse physicochemical, human health and environmental effects

No additional information available

### 2.2. Label elements

## Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) : Danger

Contains : Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Hazard statements (CLP) : H226 - Flammable liquid and vapour.

H304 - May be fatal if swallowed and enters airways.

H336 - May cause drowsiness or dizziness.

H372 - Causes damage to organs through prolonged or repeated exposure.

H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P301+P310+P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do

NOT induce vomiting. P391 - Collect spillage. P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

EUH066 - Repeated exposure may cause skin dryness or cracking.

Extra Labelling Phrases : Contains 30% or more aliphatic hydrocarbons, 15 % or over but less than 30 % aromatic

hydrocarbons, less than 5% anionic surfactants.

## 2.3. Other hazards

**EUH-statements** 

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

# **SECTION 3: Composition/information on ingredients**

# 3.1. Substances

Not Applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	EC-No.: 919-446-0 EU REACH Registration-No.: 01-2119458049-33-XXXX	≥ 80	Flam. Liq. 3, H226 STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878



Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs., compds. with 2-propanamine	CAS-No.: 84961-74-0 EC-No.: 284-664-9 EU REACH Registration-No: 01-2119985163-33-XXXX	1 – < 5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 3, H412
(2-methoxymethylethoxy)propanol substance with a Community workplace exposure limit	CAS-No.: 34590-94-8 EC-No.: 252-104-2 EU REACH Registration-No: 01-2119450011-60-XXXX	≤ 1	Not classified

Full text of H- and EUH-statements: see section 16

#### **SECTION 4: First aid measures**

A 4 F	Description	of first aid	MOCCHIROC

First-aid measures general

- : Remove victim to uncontaminated area. Call a poison center or a doctor if you feel unwell.
- Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately.

First-aid measures after skin contact

First-aid measures after inhalation

Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell. Wash clothing before reuse. Clean shoes thoroughly before reuse.

First-aid measures after eye contact

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Remove contact lenses, if present and easy to do. Continue rinsing.

First-aid measures after ingestion

Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

First-aid measures of first aiders

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

# 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects

: The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Symptoms/effects after inhalation

: At high concentrations, the vapours can be irritating to the respiratory system. May have a narcotic effect at high concentrations. Other symptoms: Headache, dizziness, nausea, unconsciousness.

Symptoms/effects after skin contact Symptoms/effects after eye contact Symptoms/effects after ingestion

- : Repeated exposure may cause skin dryness or cracking. Irritation.
- : Eye irritation. Redness.
- : Ingestion may cause nausea and vomiting. Abdominal pain, nausea. Swallowing a small quantity of this material will result in serious health hazard. Liquid with low viscosity. May result in aspiration into the lungs. Product entering lungs lead to the rapid development of very serious inhalation pulmonary lesions (medical survey during 48 hours).

## 4.3. Indication of any immediate medical attention and special treatment needed

If swallowed accidentally, the product may enter the lungs due to its low viscosity

27/09/2023 (Issue date) EU - en 3/16

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878



and lead to the rapid development of very serious pulmonary lesions (medical survey during 48 hours). Treat symptomatically.

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media : dry chemical powder, alcohol-resistant foam, carbon dioxide (CO2), Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this

material must be contained and prevented from being discharged to any waterway, sewer or

drain.

Explosion hazard : In a fire or if heated, a pressure increase will occur and the container may burst, with the

risk of a subsequent explosion.

Hazardous decomposition products in case of fire : Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other

toxic gases. Hydrocarbons. Aldehydes. Soot. Gas may accumulate in confined areas. i.e.

toxic gases can be released.

## 5.3. Advice for firefighters

Precautionary measures fire : Avoid breathing (dust, vapor, mist, gas).

Firefighting instructions : Promptly isolate the scene by removing all persons from the vicinity of the incident if

there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk.

Use water spray to keep fire-exposed containers cool..

Protection during firefighting : Wear fire/flame resistant/retardant clothing. In confined space use self-contained breathing

apparatus. Full face piece respirator.

Other information : Keep run-off water out of sewers and water sources. Containers close to fire should be

removed or cooled with water.

### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area.

### 6.1.1. For non-emergency personnel

Protective equipment : Keep unnecessary and unprotected personnel away from the spillage.

Emergency procedures : Land spill. Eliminate all ignition sources. Stop leak if safe to do so. Do not touch or walk on

the spilled product. Shut off all ignition sources.

No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is

inadequate. Put on appropriate personal protective equipment.

Measures in case of dust release : Not applicable.

## 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Wear recommended

personal protective equipment. For further information refer to section 8: "Exposure

controls/personal protection".

Emergency procedures : For further information refer to section 8: "Exposure controls/personal protection". More

detailed information: See section 11. For disposal of residues refer to section 13 : Disposal

considerations" ".

# 6.2. Environmental precautions

Avoid release to the environment. Very toxic to aquatic life with long lasting effects. Material insoluble in water. may spread in water systems. Do not discharge into drains or the environment. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

27/09/2023 (Issue date) EU - en 4/16

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878



### 6.3. Methods and material for containment and cleaning up

For containment : Eliminate sources of ignition. No open flames. No smoking.

Methods for cleaning up : Stop leak if safe to do so. Absorb excess liquid spillage on inorganic adsorbent material such as fine sand, brick dust etc. Place sport adsorbent in scaled packages and contact

such as fine sand, brick dust etc. Place spent adsorbent in sealed packages and contact specialist waste disposal contractor. Cover the spilled liquid product with foam to slow down

evaporation. Use type. Alcohol resistant foam.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Precautions for safe handling : Put on appropriate personal protective equipment (see Section 8). Do not breathe

vapour or mist. Do not swallow. Avoid contact with eyes, skin and clothing. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use

Use only non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by

explosion-proof electrical (ventilating, lighting and material handling) equipment.

earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

: 5 – 30 °C

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the

product. Do not dryhandswith rags that have been contaminated with product. Do not use

abrasives, solventsor fuels

# 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Keep locked up and out of reach of children.

Incompatible products : Oxidizing agents, acids

Heat and ignition sources : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

Storage area : Keep away from food, drink and animal feedingstuffs.

Packaging materials : Carbon steel. Glass. Mild steel. Stainless steel. high density polyethylene (HDPE).

Polyethylene terephthalate (PET).

## 7.3. Specific end use(s)

Handling temperature

Used as Paint brush cleaner (See Section 1.2). When performing aformentioned specific use, keep containers closed when not in use, keep containers upright., use only in well ventilated areas, ideally outdoors, open containers slowly in order to release any pressure build up that may occur, keep out of reach of children, apply "common sense" measures when using this product, when using transfer required amount to a suitable container such as glass, metal or HDPE and avoid all contact with skin and eyes.

## **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values


# (2-methoxymethylethoxy)propanol (34590-94-8)

#### **EU - Indicative Occupational Exposure Limit (IOEL)**

IOEL TWA 308 mg/m³, 50 ppm

27/09/2023 (Issue date) EU - en 5/16

# Safety Data Sheet





(2-methoxymethylethoxy)propanol (34590-94-8)			
Republic of Ireland - Occupational Exposure Limit (OEL)			
OEL 8h	308 mg/m³, 50 ppm	(Chemical Agents Code of Practice 2020)	
United Kingdom - Occupational Exposure Limit (OEL)			
OEL TWA	308 mg/m³, 50 ppm	(EH40/2005)	

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA 350 mg/m³		

# 8.1.2. Recommended monitoring procedures

Monitoring methods	
Monitoring methods	Workplace exposure - General requirements for the performance of procedures for the measurement of chemical agents.

## 8.1.3. Air contaminants formed

No additional information available

# 8.1.4. DNEL and PNEC

(2-methoxymethylethoxy)propanol (34590-94-8)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	283 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	308 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	36 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	37.2 mg/m³	
Long-term - systemic effects, dermal	121 mg/kg bodyweight/day	
PNEC (Water)		
PNEC aqua (freshwater)	19 mg/l	
PNEC aqua (marine water)	1.9 mg/l	
PNEC aqua (intermittent, freshwater)	190 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	70.2 mg/kg dwt	
PNEC sediment (marine water)	7.02 mg/kg dwt	
PNEC (Soil)		
PNEC soil	2.74 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	4168 mg/l	

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)		
DNEL/DMEL (Workers)		
Acute - systemic effects, inhalation	570 mg/m³	

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878



Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)		
Long-term - systemic effects, dermal	44 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	330 mg/m³/8h	
DNEL/DMEL (General population)		
Acute - systemic effects, inhalation	570 mg/m³	
Long-term - systemic effects,oral	26 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	71 mg/m³/24h	
Long-term - systemic effects, dermal	26 mg/kg bodyweight/day	
PNEC (additional information)		
Additional information PNEC is not meaningful for petroleum substances		

#### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

### Appropriate engineering controls:

Ensure good ventilation of the work station. Ensure that there is a suitable ventilation system. Mechanical ventilation is recommended. Avoid inhalation of vapours.

### 8.2.2. Personal protection equipment

### Personal protective equipment:

Do not attempt to take action without suitable protective equipment. Appropriate engineering controls.

## Personal protective equipment symbol(s):









### 8.2.2.1. Eye and face protection

# Eye protection:

Chemical goggles or safety glasses

Eye protection			
Туре	Field of application	Characteristics	Standard
Use splash goggles when eye contact due to splashing is possible	Droplet	With side shields	EN 166

## 8.2.2.2. Skin protection

## Skin and body protection:

Wear suitable protective clothing

#### Hand protection:

Wear gloves according to EN374 resistant to the solvent(s) in use.

Protective gloves. Nitrile-rubber protective gloves. Polyvinylchloride (PVC). Viton

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878



### Other skin protection

#### Materials for protective clothing:

Use appropriate personal protection equipment (PPE). According to the conditions of use, protective gloves, apron, boots, head and face protection must be worn. *E.g.* When there is a risk of ignition from static electricity, wear anti-static protective clothing; clothing should include anti-static overalls, boots and gloves

#### 8.2.2.3. Respiratory protection

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Wear respiratory protection.

Respiratory protection			
Device	Filter type	Condition	Standard
Wear respiratory protection	Type A - High-boiling (>65 °C) organic compounds, Type P2	Vapour protection	EN 405

#### 8.2.2.4. Thermal hazards

No additional information available

#### 8.2.3. Environmental exposure controls

#### **Environmental exposure controls:**

Avoid release to the environment. Do not exceed the occupational exposure limits (OEL). Assure that emissions are compliant with all applicable air pollution control regulations. Emission reduction measures for the specific use situation has to be evaluated: Gas absorbers and scrubbers for relatively small volume structures. Minimisation of the fumigated volume by inflated balloons for large volume structure (e.g. churches, houses). (fumigation). Control measures to prevent releases. Keep container tightly closed. Dispose of this material and its container at hazardous or special waste collection point.

#### Other information:

Pregnant/breastfeeding women working with the product must not be in direct contact with the product. Persons suffering from asthma or eczema and persons who have chronic lung diseases, skin or respiratory allergies to isocyanates should not work with the material.

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour Blue. Liquid. Appearance characteristic. Odour Odour threshold Not available Melting point Not applicable Freezing point : Not available 158 - 191 °C Boiling point Not available Flammability Lower explosion limit : 0.7% Upper explosion limit

Flash point :  $\approx 40$  °C ISO 13736

Solubility : Main Substance in mixture is a UVCB. Standard tests for this endpoint are not appropriate.

Partition coefficient n-octanol/water (Log Kow) : Not available Vapour pressure : 1.9 hPa @20 °C Vapour pressure at 50 °C : Not available Not available Density Relative density 0.763 - 0.803Relative vapour density at 20 °C : Not available Particle characteristics Not applicable Explosive properties Not applicable Oxidising properties Not available **Evaporation Rate** : 57 (ether = 1)

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878



## 9.2. Other information

### 9.2.1. Information with regard to physical hazard classes

No additional information available

### 9.2.2. Other safety characteristics

Relative evaporation rate (ether=1) :  $\approx 57$ VOC content :  $\leq 769$  g/l

# SECTION 10: Stability and reactivity

## 10.1. Reactivity

Flammable liquid and vapour.

# 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

## 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. Never pressurise packagings as they will not resist.

# 10.5. Incompatible materials

Acids. Oxidizing agent.

## 10.6. Hazardous decomposition products

Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot.

# **SECTION 11: Toxicological information**


## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Based on available data, the classification criteria are not met
Acute toxicity (dermal) : Based on available data, the classification criteria are not met
Acute toxicity (inhalation) : Based on available data, the classification criteria are not met

Hydrocarbons, C9-C12, n-alkanes, isoalkanes	, cyclics, aromatics (2-25%)	
LD50 oral	> 15000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)	
LC50 Inhalation (vapour)	> 13.1 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)	
LD50 dermal	> 3400 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute D Toxicity)	

(2-methoxymethylethoxy)propanol (34590-94-8)		
LD50 oral	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)	
LD50 dermal	> 19020 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	

## Safety Data Sheet





(2-methoxymethylethoxy)propanol (34590-94-8)		
	9510 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
LC50 inhalation (vapour)	> 275 ppm Animal: rat, , Guideline: OECD Guideline 402 (Acute Inhalation Toxicity)	

Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs., compds. with 2-propanamine (84961-74-0)		
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EU Method B.1 bis (Acute Oral Toxicity - Fixed Dose Procedure), OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)	
Skin corrosion/irritation	: Based on available data, the classification criteria are not met	

# Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs., compds. with 2-propanamine (84961-74-0)

Causes skin irritation.

Positive result, relative mean tissue viability = 6.8% (which is < 50%), in vitro method, Guideline

 $OECD\ Guideline\ 439\ (In\ Vitro\ Skin\ Irritation:\ Reconstructed\ Human\ Epidermis\ Test\ Method)\ )\ and\ EU\ Method\ B.46\ (In\ Vitro\ Skin\ Irritation:\ Reconstructed\ Human\ Epidermis\ Test\ Method)\ )$ 

Reconstructed Human Epidermis Model Test)

Serious eye damage/irritation : Based on available data, the classification criteria are not met

pH: Not applicable

# Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs., compds. with 2-propanamine (84961-74-0)

Causes serious eye irritation.

Respiratory or skin sensitisation : Based on available data, the classification criteria are not met

Germ cell mutagenicity : Based on available data, the classification criteria are not met

Carcinogenicity : Based on available data, the classification criteria are not met

Reproductive toxicity : Based on available data, the classification criteria are not met

STOT-single exposure : May cause drowsiness or dizziness.

STOT-single exposure : May cause drowsiness or dizziness.		
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)		
STOT-single exposure	May cause drowsiness or dizziness.	
STOT-repeated exposure : Causes damage to organs through prolonged or repeated exposure.		
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)		
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.	
Aspiration hazard : May be fatal if swallowed and enters airways.		
Arc Brush Cleaner		
Viscosity, kinematic 35 mm²/s (B2 FLOW CUP)		

### 11.2. Information on other hazards

## 11.2.1 Endocrine Disrupting Properties

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

#### 11.2.2 Other Information

No additional information available

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878



# SECTION 12: Ecological information

## 12.1. Toxicity

Hazardous to the aquatic environment, short-term

(acute)

Hazardous to the aquatic environment, long-term

(chronic)

: Based on available data, the classification criteria are not met

: Toxic to aquatic life with long lasting effects.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)			
LC50 96h - Fish	> 10 - 30 mg/l Test organisms (species): Oncorhynchus mykiss, Guideline: OECD Guideline 203		
EC50 48h – Daphnia magna	> 10 - 22 mg/l Test organisms (species): Daphnia magna, Guideline: OECD Guideline 202		
EC50 72h – Algae	4.1 mg/l Test organisms (species): Pseudokirchneriella subcapitata, Guideline: OECD Guideline 201		
EC50 72h – Algae	4.6 -10 mg/l Test organisms (species): Pseudokirchneriella subcapitata, Guideline: OECD Guideline 201		
NOEC 72 h & NOEC 96 h – Algae	0.16 mg/l Test organisms (species): Pseudokirchneriella subcapitata, Guideline: OECD Guideline 201		
NOEC 21 d - Daphnia magna	0.097 mg/l Test organisms (species): Oncorhynchus mykiss, Guideline: OECD Guideline 211		

enzenesulfonic acid, 4-C10-13-sec-alkyl derivs., compds. with 2-propanamine (84961-74-0)		
EC50 48h – Daphnia magna	7.1 mg/l Test organisms (species): Oncorhynchus mykiss, Guideline: OECD Guideline 202	
NOEC 72h – Algae	7.5 mg/l Test organisms (species): Raphidocelis subcapitata, Guideline: OECD Guideline 201	

2-methoxymethylethoxy)propanol (34590-94-8)		
LC50 96h - Fish	> 1000 mg/l Test organisms (species): Poecilia reticulata, Guideline: OECD Guideline 203	
EC50 72h – Algae	> 969 mg/L Test organisms (species): Raphidocelis subcapitata, Guideline: OECD Guideline 203	

# 12.2. Persistence and degradability

Product is readily biodegradable

Toduct is readily blodegradable		
Arc Brush Cleaner		
Persistence and degradability	The surfactant(s) contained in this product complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents.  More specifically Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs., compds. with 2-propanamine (84961-74-0): 81.21% degradation (CO2 evolution) at 10 d, 87.35% degradation (CO2 evolution) at 28 d, OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test), hence surfactant is readily biodegradable.	

Hydrocarbons, C9-C12, n-alkanes, isoalkanes	ocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)		
Read Across from reference substance Hydrocarbons, C10 - C13, n-alkanes, isoalkanes, cyclics, aromatics (2 -25%)	74.7% biodegraded at 28 d, Guideline: OECD Guideline 301 F. Reference substance concluded to be readily biodegradable.		

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878



# (2-methoxymethylethoxy)propanol (34590-94-8)

Persistence and degradability 75% degradation at 10 d (O2 Consumption).

96% degradation at 28 d (DOC Removal). 76% degradation at 28 d (CO<sub>2</sub> evolution).

Guideline: OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry

### 12.3. Bioaccumulative potential

No additional information available on mixture

### Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Standard Bioaccumulation studies for this endpoint are intended for monoconstituent substances and are not appropriate for petroleum UVCB substances.

### Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs., compds. with 2-propanamine (84961-74-0)

derivs., sodium salts (CAS: 68411-30-3)

Read Across from Benzenesulfonic acid, C10-13-alkyl BCF = 2 - 1000 L/kg Guideline: OECD Guideline 305 E (Bioaccumulation: Flow-through Fish Test). Results show that the bioconcentration potential of LAS is low

## (2-methoxymethylethoxy)propanol (34590-94-8)

Has a low log Kow (log Kow< 1) and is readily biodegradable, which suggests that this substance is not expected to accumulate in biological tissues or bioaccumulate in foodwebs

## 12.4. Mobility in soil

No additional information available

#### 12.5. Results of PBT and vPvB assessment

This mixture does not to contain any substances at a concentration ≥ 0.1% that are considered to be PBT and vPvB.

## 12.6. Endocrine disrupting properties

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

### 12.7. Other adverse effects

There are no other known adverse effects, as of yet, for this mixture.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

This product *is* classified as Hazardous Waste as it is supplied.

Waste generation should be avoided or minimised where possible. When handling waste, the safety precautions applying to handling of the product should be considered. Label the containers containing waste and remove from the area as soon as possible. Label the containers containing waste contaminated material and remove from the area as soon as possible.

Product disposal to sewer should be avoided, if possible, and only be carried out after treatment, and under relevant rules, e.g. Consent to Discharge. Where wastes undergo disposal, external recovery or treatment, it must comply with the requirements of environmental protection, waste disposal legislation and any local authority requirements. If wastes undergo incineration, they must be suitable for it at an approved facility.

Used packaging waste should be reused or recycled, if uncontaminated. Contaminated packaging should be cleaned on site, if appropriate facilities exist, including any relevant rules or permits, or offsite by a specialist provider. Contaminated packaging which cannot be safely cleaned must be treated in the same way as the product, and should only be disposed of as a last resort.

List of waste code is 20 01 29\* - detergents containing hazardous substances . These codes have been assigned based on the actual composition of the product as supplied. Seek advice from a hazardous waste specialist for waste classification.

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878



# **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID		
14.1. UN number or ID number						
UN 1263	UN 1263	UN 1263	UN 1263	UN 1263		
14.2. UN proper shippin	14.2. UN proper shipping name					
PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	Paint related material	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL		
Transport document descr	iption					
UN 1263 PAINT RELATED MATERIAL, 3, III, (E), ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT RELATED MATERIAL, 3, III, MARINE POLLUTANT	UN 1263 Paint related material, 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT RELATED MATERIAL, 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT RELATED MATERIAL, 3, III, ENVIRONMENTALLY HAZARDOUS		
14.3. Transport hazard o	class(es)					
3	3	3	3	3		
<b>1 1 1 1 1 1 1 1 1 1</b>	3	3	**************************************	<b>№ №</b>		
14.4. Packing group						
III	III	III	III	III		
14.5. Environmental hazards						
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes		
No supplementary information	, i					

## 14.6. Special precautions for user

### **Overland transport**

Classification code (ADR) : F1

Special provisions (ADR) : 163, 367, 650

Limited quantities (ADR) : 5I Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, R001
Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Transport category (ADR) : 3
Special provisions for carriage - Operation (ADR) : S2

Special provisions for carriage - Operation (ADR) : S2 Tunnel restriction code (ADR) : E

# Transport by sea

Special provisions (IMDG) : 163, 223, 367, 955

Limited quantities (IMDG) : 5 L : E1 Excepted quantities (IMDG) : P001, LP01 Packing instructions (IMDG) Special packing provisions (IMDG) : PP1 IBC packing instructions (IMDG) : IBC03 : T2 Tank instructions (IMDG) Tank special provisions (IMDG) : TP1, TP29 : F-E EmS-No. (Fire) : S-E EmS-No. (Spillage)

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878



Stowage category (IMDG) : A

Properties and observations (IMDG) : Miscibility with water depends upon the composition.

#### Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y344
PCA limited quantity max net quantity (IATA) : 10L
PCA packing instructions (IATA) : 355
PCA max net quantity (IATA) : 60L
CAO packing instructions (IATA) : 366
CAO max net quantity (IATA) : 220L

Special provisions (IATA) : A3, A72, A192

ERG code (IATA) : 3L

## Inland waterway transport

Classification code (ADN) : F1

Special provisions (ADN) : 163, 367, 650

Limited quantities (ADN) : 5 L

Excepted quantities (ADN) : E1

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01

Number of blue cones/lights (ADN) : 0

### Rail transport

Classification code (RID) : F1

Special provisions (RID) : 163, 367, 650

Limited quantities (RID) : 5L

Excepted quantities (RID) : E1

Packing instructions (RID) : P001, IBC03, LP01, R001

Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T2
Portable tank and bulk container special provisions : TP1, TP29

(RID)

Tank codes for RID tanks (RID) : LGBF
Transport category (RID) : 3
Special provisions for carriage – Packages (RID) : W12
Colis express (express parcels) (RID) : CE4
Hazard identification number (RID) : 30

## 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## 15.1.1. EU-Regulations

## **REACH Annex XVII (Restriction List)**

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

## **REACH Candidate List (SVHC)**

Contains no substance(s) listed on the REACH Candidate List

#### **PIC Regulation (Prior Informed Consent)**

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878



#### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

## Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

### VOC Directive (2004/42)

VOC content :  $\leq$  769 g/l

### **Explosives Precursors Regulation (2019/1148)**

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

#### **Drug Precursors Regulation (273/2004)**

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### **Detergent Regulation ((EC) No 648/2004**

Product is under the scope of this regulation.

### 15.2. Chemical safety assessment

A Chemical safety assessment has not been done for this mixture.

## **SECTION 16: Other information**

#### Indication of changes:

Due to change of classification database the revision numbering has been reset. You should therefore look at the revision date rather than the revision number to ensure you have the most up to date version.

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

# Safety Data Sheet



