Regulation EC No 1907/2006 Art.31

Productname: WG-90 Creationdate: 29.06.17 Version: 1.1

Ref.Nr.: UDS000828 3 20170629 (EN) Replaces: UDS000828 20170511

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

WG-90

Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Lubricants

1.3. Details of the supplier of the safety data sheet

CRC Industries UK Ltd. Wylds Road Castlefield Industrial Estate TA6 4DD Bridgwater Somerset United Kingdom

Tel.: +44 1278 727200 Fax.: +44 1278 425644 E-mail: hse.uk@crcind.com

1.4. Emergency telephone number

(+44)(0)1278 72 7200 (office hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Physical: Aerosols, category 1

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Classification is based on test data.

Health: Skin irritation, category 2 Causes skin irritation.

Specific target organ toxicity - single exposure, category 3

May cause drowsiness or dizziness.

Classification based on calculation method.

Environment: Hazardous to the aquatic environment, chronic category 3

Harmful to aquatic life with long lasting effects.

Classification based on calculation method.



1/9

CRC Industries UK Limited

Regulation EC No 1907/2006 Art.31

 Productname :
 WG-90
 Creationdate :
 29.06.17 Version : 1.1

 Ref.Nr.:
 UDS000828 3 20170629 (EN)
 Replaces:
 UDS000828 20170511

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008

Product identifier: Contains:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Hazard pictogram(s):

• (!)

Signal word: Danger

Hazard statement(s): H222 : Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H315 : Causes skin irritation.

H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

Precautionary statement(s): P102 : Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P261 : Avoid breathing dust/fume/gas/mist/vapours/spray. P271 : Use only outdoors or in a well-ventilated area.

P410/412 : Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F.

P501-2: Dispose of contents/container to an authorised waste collection point.

2.3. Other hazards

No information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable.

3.2. Mixtures

| Hazardous ingredient | Registration number | CAS- nr. | EC-nr | w/w % | Hazard Class and Category | Hazard statement | Notes |
|--|--------------------------|----------------|-----------------|-----------|---|--------------------------|-------|
| Hydrocarbons,C3-4-rich, petroleum distillate Petroleumgas (1,3-butadiene < 0.1%) | 01- 2119485926- 20 | 68512- 91-4 | 270- 990-9 | 30- 60 | Press. Gas, Flam. Gas 1 | H280,H220 | K,G |
| Hydrocarbons, C6-C7, n- alkanes,isoalkanes,cyclics,< 5% n- hexane | 01- 2119475514- 35 | - | (921- 024-6) | <25 | Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2 | H225,H315,H336,H304,H411 | B,Q |
| zinc oxide | 01- 2119463881- 32 | 1314- 13-2 | 215- 222-5 | <2 | Aquatic Acute 1, Aquatic Chronic 1 | H400,H410 | В |



Regulation EC No 1907/2006 Art.31

WG-90 Creationdate: 29.06.17 Version: 1.1 Productname:

Ref.Nr.: UDS000828 3 20170629 (EN) Replaces: UDS000828 20170511

Explanation notes

B: substance with national established workplace exposure limit

G: exempted from the obligation to register in accordance with art.2(7) of REACH Regulation No 1907/2006

K: not classified as carcinogen, less than 0.1% w/w 1,3-butadiene (Einecs-nr. 203-450-8)

Q: The CAS-no is only an indicative identifier to be used outside the EU for global inventory entries.

(* Explanation phrases : see chapter 16)

SECTION 4: First aid measures

4.1. Description of first aid measures

Contact with eyes: If substance has got into eyes, immediately wash out with plenty of water

If eye irritation persists: Get medical advice/attention.

Contact with skin: Take off contaminated clothing and wash before reuse.

> IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

Inhalation: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell.

If swallowed do not induce vomiting because of risk of aspiration into the Ingestion:

lungs. If aspiration is suspected obtain immediate medical attention

4.2. Most important symptoms and effects, both acute and delayed

Inhalation: Excessive inhalation of solvent vapours may give rise to nausea, headaches

and dizziness

Ingestion: After vomiting of swallowed product aspiration into lungs is likely. Solvents

may induce chemical pneumonia.

Symptoms: sore throat, abdominal pain, nausea, vomiting

Skin contact: Irritating to skin

Symptoms: redness and pain

Eye contact: May cause irritation.

Symptoms: redness and pain

4.3. Indication of any immediate medical attention and special treatment needed

General Advice: If you feel unwell, seek medical advice (show the label where possible

If symptoms persist always call a doctor

SECTION 5: Firefighting measures

5.1. Extinguishing media

foam, carbon dioxide or dry agent

5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C



3/9

Regulation EC No 1907/2006 Art.31

 Productname :
 WG-90
 Creationdate :
 29.06.17 Version : 1.1

 Ref.Nr.:
 UDS000828 3 20170629 (EN)
 Replaces:
 UDS000828 20170511

Forms hazardous decomposition products CO,CO2

5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water In case of fire, do not breathe fumes

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources Ensure adequate ventilation Wear suitable protective clothing and gloves.

6.2. Environmental precautions

Do not allow to enter public sewers and watercourses

6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material

6.4. Reference to other sections

For further information see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

Equipment should be earthed

Use explosion-proof electrical/ventilating/lighting/.../equipment.

Use only non-sparking tools.

Do not breathe aerosols or vapours.

Ensure adequate ventilation

Avoid contact with skin and eyes.

Wash thoroughly after use

Wear protective gloves/protective clothing/eye protection/face protection.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Keep out of reach of children.



Regulation EC No 1907/2006 Art.31

WG-90 Creationdate: 29.06.17 Version: 1.1 Productname:

Ref.Nr.: Replaces: UDS000828 3 20170629 (EN) UDS000828 20170511

7.3. Specific end use(s)

Lubricants

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits:

No information available

8.2. Exposure controls

Ensure adequate ventilation Control procedures :

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

Take precautions to avoid contact with skin and eyes when handling the Personal protection:

product.

In all cases handle and use the product in accordance with good industrial

hygiene practices.

Ensure adequate ventilation

inhalation: In case of insufficient ventilation, wear suitable respiratory equipment.

hands and skin: When handling the product wear chemical-resistant gloves (standard EN 374).

Use a reusable glove with a minimum breakthrough time of 30 minutes. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be

changed part-way through.

Recommended gloves: Nitrile

eyes: Wear safety eyewear according to EN 166.

Environmental protection: Avoid release to the environment.

Collect spillage.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

(for aerosols data for the product without propellant)

Propane/butane propelled liquid. Apperance : physical state :

colour: Off-white.

Characteristic odor. odour: pH: Not applicable.

Boiling point/range: 63 °C - 26 °C Flash point: Evaporation rate: Not available.

Explosion limits: upper limit: 9.4 % lower limit: 1.1 %



Regulation EC No 1907/2006 Art.31

 Productname :
 WG-90
 Creationdate :
 29.06.17 Version : 1.1

 Ref.Nr.:
 UDS000828_3_20170629 (EN)
 Replaces:
 UDS000828_20170511

Vapour pressure : Not available.

Relative density: 0.797 g/cm3 (@ 20°C).

Solubility in water: Insoluble in water

Auto-ignition: > 200 Not available.

Viscosity: Not available.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions known if used for its intended purpose

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

10.4. Conditions to avoid

Avoid overheating

10.5. Incompatible materials

Strong oxidising agent

10.6. Hazardous decomposition products

CO,CO2

SECTION 11: Toxicological information

11.1. Information on toxicological effects

acute toxicity: based on available data the classification criteria are not met skin corrosion/irritation: Causes skin irritation. serious eye damage/irritation: based on available data the classification criteria are not met respiratory or skin based on available data the classification criteria are not met sensitisation: based on available data the classification criteria are not met germ cell mutagenicity: based on available data the classification criteria are not met carcinogenicity: toxicity for reproduction: based on available data the classification criteria are not met STOT-single exposure: May cause drowsiness or dizziness.



6/9

CRC Industries UK Limited

Regulation EC No 1907/2006 Art.31

 Productname :
 WG-90
 Creationdate :
 29.06.17 Version : 1.1

 Ref.Nr.:
 UDS000828 3 20170629 (EN)
 Replaces:
 UDS000828 20170511

STOT repeated exposure: based on available data the classification criteria are not met based on available data the classification criteria are not met

Information on likely routes of exposure:

Inhalation: Inhalation of solvent vapours may give rise to nausea, headaches and

dizziness

Ingestion: After vomiting of swallowed product aspiration into lungs is likely. Solvents

may induce chemical pneumonia.

Skin contact : Irritating to skin **Eye contact :** May cause irritation.

Toxicological data:

| Hazardous ingredient | CAS-nr. | method | |
|---|-----------|----------------|---------------|
| zinc oxide | 1314-13-2 | LC50 inhal.rat | > 5.7 mg/l |
| Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane | - | LD50 oral rat | > 5000 mg/kg |
| | | LC50 inhal.rat | > 25000 mg/m3 |
| | | LD50 derm.rat | > 2000 mg/kg |

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, chronic category 3 Harmful to aquatic life with long lasting effects.

Ecotoxicological data:

| Hazardous ingredient | CAS-nr. | method | |
|---|-----------|--------------|------------|
| zinc oxide | 1314-13-2 | IC50 algae | 0.136 mg/l |
| | | LC50 fish | 0.169 mg/l |
| | | EC50 daphnia | 1.7 mg/l |
| Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane | - | LC50 fish | > 10 mg/l |
| | | EC50 daphnia | 3 mg/l |

12.2. Persistence and degradability

No information available

12.3. Bioaccumulative potential

No information available

12.4. Mobility in soil



Regulation EC No 1907/2006 Art.31

Productname: WG-90

Creationdate: 29.06.17 Version: 1.1 Ref.Nr.: UDS000828 3 20170629 (EN) Replaces: UDS000828 20170511

Insoluble in water

12.5. Results of PBT and vPvB assessment

No information available

12.6. Other adverse effects

No information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product: This material and its container must be disposed of in a safe way.

Do not discharge into drains or the environment, dispose to an authorised

waste collection point.

Disposal should be in accordance with local, state or national legislation Contaminated packaging :

SECTION 14: Transport information

14.1. UN number

UN-number: 1950

14.2. UN proper shipping name

Proper shipping name: **AEROSOLS**

14.3. Transport hazard class(es)

Class: 2.1 ADR/RID - Classification code: 5F

14.4. Packing group

Packing group: Not applicable.

14.5. Environmental hazards

ADR/RID - Environmentally No hazardous: IMDG - Marine pollutant: No IATA/ICAO - Environmentally No hazardous:

14.6. Special precautions for user



8/9

Regulation EC No 1907/2006 Art.31

 Productname :
 WG-90
 Creationdate :
 29.06.17 Version : 1.1

 Ref.Nr.:
 UDS000828_3_20170629 (EN)
 Replaces:
 UDS000828_20170511

| ADR/RID - Tunnelcode: | (D) |
|-----------------------|----------|
| IMDG - Ems: | F-D, S-U |
| IATA/ICAO - PAX: | 203 |
| IATA/ICAO - CAO | 203 |

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.

Regulation (EC) No 1907/2006 (REACH)

Regulation (EC) No 1272/2008 (CLP)

Dir. 2013/10/EU, 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.

15.2. Chemical safety assessment

No information available

SECTION 16: Other information

*Explanation hazard statements: H220: Extremely flammable gas.

H225: Highly flammable liquid and vapour.

H280: Contains gas under pressure; may explode if heated.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H400: Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects. H411 : Toxic to aquatic life with long lasting effects.

acronyms and synonyms: TWA = time weight average

STEL = short time exposure limit VOC = volatile organic compounds PBT = persistant bioaccumulative toxic vPvB = very persitant very bioaccumulative

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

