

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Version: 3.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product form : Mixture

: TECH WHITE RADIATOR RAL 9010 Name

Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public

Use of the substance/mixture : Spraying paint (spray can)

Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Novasol Spray, S.A.

P.I.: Empalme - C/ Empalme, 27 Llorenç del Penedès - Spain

T +34 977 677 305

novasol@novasolspray.com - www.novasolspray.com

Emergency telephone number

Emergency number : +34 977 677 305

Office hours: Monday-Friday 8:30 AM-6:00 PM GMT+1

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222:H229 Serious eye damage/eye irritation, Category H319

Specific target organ toxicity — Single H336

exposure, Category 3, Narcosis

Full text of H statements: see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes serious eye irritation.

Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS02

Signal word (CLP) : Danger

Hazardous ingredients : n-butyl acetate; ethyl acetate; butanone Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness.

Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P271 - Use only outdoors or in a well-ventilated area.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P280 - Wear protective gloves.

FUH-statements : EUH066 - Repeated exposure may cause skin dryness or cracking.

1/9 28/05/2018 EN (English)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Security closing plug for children : Not applicable Tactile warning : Not applicable

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ethyl acetate	(CAS-No.) 141-78-6 (EC-No.) 205-500-4 (EC Index-No.) 607-022-00-5 (REACH-no) 01-2119475103-46	10 - 15	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
xylene	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index-No.) 601-022-00-9 (REACH-no) 01-2119488216-32	7 - 10	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
butanone	(CAS-No.) 78-93-3 (EC-No.) 201-159-0 (EC Index-No.) 606-002-00-3 (REACH-no) 01-2119457290-43	7 - 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Titaniumoxide substance with a Community workplace exposure limit	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5 (REACH-no) 01-2119489379-17	< 10	Not classified
n-butyl acetate substance with a Community workplace exposure limit	(CAS-No.) 123-86-4 (EC-No.) 204-658-1 (EC Index-No.) 607-025-00-1 (REACH-no) 01-2119485493-29	3 - 5	Flam. Liq. 3, H226 STOT SE 3, H336
ethylbenzene	(CAS-No.) 100-41-4 (EC-No.) 202-849-4 (EC Index-No.) 601-023-00-4	1 - 3	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Repeated exposure may cause skin dryness or cracking

Symptoms/effects after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

Hazardous decomposition products in case of

fire

28/05/2018 EN (English) 2/9

: Toxic fumes may be released.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

5.3. Advice for firefighters

Protection during firefighting

 Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures

: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing

dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

: Mechanically recover the product.

Other information

: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing

dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective

equipment.

Hygiene measures

Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Conditions for safe storage, including any incompatibilities

Storage conditions

: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

n-butyl acetate (123-86-4)					
EU	Local name	n-butyl acetate			
EU	Notes	(Ongoing)			
EU	Regulatory reference	SCOEL Recommendations			
ethyl acetate (141-78-6)					
EU	Local name	Ethyl acetate			
EU	IOELV TWA (mg/m³)	734 mg/m³			
EU	IOELV TWA (ppm)	200 ppm			
EU	IOELV STEL (mg/m³)	1468 mg/m³			
EU	IOELV STEL (ppm)	400 ppm			
EU	Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164			
butanone (78-93-3)	butanone (78-93-3)				
EU	Local name	Butanone			
EU	IOELV TWA (mg/m³)	600 mg/m³			
EU	IOELV TWA (ppm)	200 ppm			
EU	IOELV STEL (mg/m³)	900 mg/m³			
EU	IOELV STEL (ppm)	300 ppm			
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC			
xylene (1330-20-7)					
EU	Local name	Xylene, mixed isomers, pure			
EU	IOELV TWA (mg/m³)	221 mg/m³			
EU	IOELV TWA (ppm)	50 ppm			

28/05/2018 EN (English) 3/9

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

xylene (1330-20-7)				
EU	IOELV STEL (mg/m³)	442 mg/m³		
EU	IOELV STEL (ppm)	100 ppm		
EU	Notes	Skin		
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC		
ethylbenzene (100-41-4)	ethylbenzene (100-41-4)			
EU	Local name	Ethylbenzene		
EU	IOELV TWA (mg/m³)	442 mg/m³		
EU	IOELV TWA (ppm)	100 ppm		
EU	IOELV STEL (mg/m³)	884 mg/m³		
EU	IOELV STEL (ppm)	200 ppm		
EU	Notes	Skin		
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC		
Titaniumoxide (13463-67-7)				
EU	Local name	Titanium dioxide		
EU	Notes	(Ongoing)		
EU	Regulatory reference	SCOEL Recommendations		

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Hand protection:

Butyl rubber gloves (EN 374)

Eye protection:

eye protection (EN166)

Respiratory protection:

If vapour is released : Disposable half mask

Personal protective equipment symbol(s):





Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Informatio	n on basic physical	and chemical properties
-----------------	---------------------	-------------------------

Physical state : Liquid Colour : Various.

Odour : No data available : No data available Odour threshold : No data available Relative evaporation rate (butylacetate=1) : No data available Melting point : Not applicable Freezing point : No data available : < 0 °C Aerosol jet Boiling point : < -60 °C Aerosol jet Flash point Auto-ignition temperature : No data available Decomposition temperature : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Vapour pressure : No data available
Relative vapour density at 20 °C : No data available
Relative density : No data available

28/05/2018 EN (English) 4/9

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Solubility : No data available
Log Pow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available

Explosive properties : Pressurised container: May burst if heated.

Oxidising properties : No data available Explosive limits : No data available

9.2. Other information

 Not volatile
 : 18 wt%

 VOC content
 : 82 wt%

 VOC content
 : 620 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

ethylbenzene (100-41-4)

LD50 oral

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

n-butyl acetate (123-86-4)		
LD50 oral	10760	
LD50 dermal	> 14112	
LC50 inhalation rat (mg/l)	23,4	
ethyl acetate (141-78-6)		
LD50 oral rat	4100 mg/kg	
LD50 dermal rabbit	20000 mg/kg	
LD50 dermal	>	
LC50 inhalation rat (mg/l)	> 44 g/m³	
LC50 inhalation rat (Vapours - mg/l/4h)	22,5 mg/l/4h	
butanone (78-93-3)	butanone (78-93-3)	
LD50 oral	>0	
LD50 dermal rat	4000 mg/kg	
LD50 dermal rabbit	6400 mg/kg	
LD50 dermal	> 5000	
LC50 inhalation rat (mg/l)	23,5	
xylene (1330-20-7)		
LD50 oral	3523 mg/kg	
LD50 dermal rabbit	12126 mg/kg	
LD50 dermal	1100 mg/kg	
LC50 inhalation rat (mg/l)	27,124 mg/l/4h	
LC50 inhalation rat (Vapours - mg/l/4h)	27,12 mg/l/4h	

28/05/2018 EN (English) 5/9

3500

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ethylbenzene (100-41-4)	
LC50 inhalation rat (mg/l)	17,2
Titaniumoxide (13463-67-7)	
LD50 oral	> 10000 mg/kg
LD50 dermal	> 10000 mg/kg
LC50 inhalation rat (mg/l)	> 6,8 mg/l/4h
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified

STOT-single exposure : May cause drowsiness or dizziness.

xylene (1330-20-7)		
NOAEL (oral, rat)	250 mg/kg bodyweight	
STOT-repeated exposure	: Not classified	
Aspiration hazard	: Not classified	
TECH WHITE RADIATOR RAL 9010		
Vaporizer	Aerosol	

SECTION 12: Ecological information

		_			
и	2.1	т	~~	ri o	itv
۰	Z .	-	U)	u.	ILV

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse

effects in the environment.

Acute aquatic toxicity : Not classified Chronic aquatic toxicity : Not classified

butanone (78-93-3)	
LC50 fish 1	3220 mg/l
EC50 Daphnia 1	5091 mg/l
xylene (1330-20-7)	
EC50 other aquatic organisms 1	> 3,4 mg/l
Titaniumoxide (13463-67-7)	
LC50 fich 1	> 1000 mg/l

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

28/05/2018 EN (English) 6/9

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA		
14.1. UN number				
1950	1950	1950		
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable		
Transport document description				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1		
14.3. Transport hazard class(es)				
2.1	2.1	2.1		
2	2	2		
14.4. Packing group				
Not applicable	Not applicable	Not applicable		
14.5. Environmental hazards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No		
No supplementary information available				

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 11 Excepted quantities (ADR) : E0 Packing instructions (ADR) : P207

: PP87, RR6, L2 Special packing provisions (ADR)

Mixed packing provisions (ADR) : MP9 Transport category (ADR) : 2 Special provisions for carriage - Packages : V14 (ADR)

Special provisions for carriage - Loading,

unloading and handling (ADR)

Special provisions for carriage - Operation

(ADR)

Tunnel restriction code (ADR) : D

- Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

: CV9, CV12

: S2

Packing instructions (IMDG) : P207, LP200 Special packing provisions (IMDG) : PP87, L2 EmS-No. (Fire) : F-D EmS-No. (Spillage) : S-U Stowage category (IMDG) : None Stowage and handling (IMDG) : SW1, SW22 Segregation (IMDG) : SG69

- Air transport

PCA Excepted quantities (IATA) : E0 PCA Limited quantities (IATA) : Y203 PCA limited quantity max net quantity (IATA) : 30kgG PCA packing instructions (IATA) : 203 PCA max net quantity (IATA) : 75kg CAO packing instructions (IATA) : 203 CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

28/05/2018 EN (English) 7/9

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ERG code (IATA) : 10L

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	n-butyl acetate - ethyl acetate - butanone - xylene - ethylbenzene
3(a) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	TECH WHITE RADIATOR RAL 9010 - n-butyl acetate - ethyl acetate - butanone - xylene - ethylbenzene
3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	TECH WHITE RADIATOR RAL 9010 - ethyl acetate - butanone - xylene - ethylbenzene
40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	n-butyl acetate - ethyl acetate - butanone - xylene - ethylbenzene

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 82 wt%

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830.

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.

28/05/2018 EN (English) 8/9

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH066	Repeated exposure may cause skin dryness or cracking.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

28/05/2018 EN (English) 9/9