

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Version: 3.0

| SECTION 1: Identification of the | substance/mixture and of the company/undertaking | |
|---|--|--|
| 1.1. Product identifier | | |
| Product form | : Mixture | |
| Name | : TECH WHITE HOUSEHOLD RAL 9016 | |
| Vaporizer | : Aerosol | |
| | | |
| 1.2. Relevant identified uses of the | substance or mixture and uses advised against | |
| 1.2.1. Relevant identified uses | | |
| Intended for general public | | |
| Use of the substance/mixture | : Spraying paint (spray can) | |
| 1.2.2. Uses advised against | | |
| No additional information available | | |
| 1.3. Details of the supplier of the sa | ifety data sheet | |
| Novasol Spray, S.A. P.I.: Empalme - C/ Empalme, 27 Llorenç del Penedès - Spain T +34 977 677 305 novasol@novasolspray.com - www.novasol | Ispray.com | |
| 1.4. Emergency telephone number | | |
| Emergency number | : +34 977 677 305 Office hours: Monday-Friday 8:30 AM-6:00 PM GMT+1 | |
| SECTION 2: Hazards identification | bn | |
| 2.1. Classification of the substance | or mixture | |
| Classification according to Regulation (E | EC) No. 1272/2008 [CLP] | |
| Aerosol, Category 1 | H222;H229 | |
| Serious eye damage/eye irritation, Category | y H319 | |
| Specific target organ toxicity — Single exposure, Category 3, Narcosis | H336 | |
| Full text of H statements : see section 16 | | |
| | | |
| Adverse physicochemical, human health and environmental effects Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes serious eye irritation. | | |
| 2.2. Label elements | | |
| Labelling according to Regulation (EC) N | lo. 1272/2008 [CLP] | |
| Hazard pictograms (CLP) | : GHS02 GHS07 | |
| Signal word (CLP) | : Danger | |
| Hazardous ingredients | : n-butyl acetate; ethyl acetate; butanone | |
| Hazard statements (CLP) | H222 - Extremely flammable aerosol. H229 - Pressurised container: May burst if heated. H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness. | |
| Precautionary statements (CLP) | P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. | |

: EUH066 - Repeated exposure may cause skin dryness or cracking.

- P251 Do not pierce or burn, even after use. P271 Use only outdoors or in a well-ventilated area.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P280 Wear protective gloves.

EUH-statements

28/05/2018

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| Security closing plug for children | : Not applicable |
|------------------------------------|------------------|
| Tactile warning | : Not applicable |

2.3. Other hazards No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|--|---|---------|---|
| ethyl acetate | (CAS-No.) 141-78-6 (EC-No.) 205-500-4 (EC Index-No.) 607-022-00-5 (REACH-no) 01-2119475103-46 | 10 - 15 | Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 |
| xylene | (CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index-No.) 601-022-00-9 (REACH-no) 01-2119488216-32 | 7 - 10 | Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 |
| butanone | (CAS-No.) 78-93-3 (EC-No.) 201-159-0 (EC Index-No.) 606-002-00-3 (REACH-no) 01-2119457290-43 | 7 - 10 | Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 |
| Titaniumoxide substance with a Community workplace exposure limit | (CAS-No.) 13463-67-7 (EC-No.) 236-675-5 (REACH-no) 01-2119489379-17 | < 10 | Not classified |
| n-butyl acetate substance with a Community workplace exposure limit | (CAS-No.) 123-86-4 (EC-No.) 204-658-1 (EC Index-No.) 607-025-00-1 (REACH-no) 01-2119485493-29 | 3 - 5 | Flam. Liq. 3, H226 STOT SE 3, H336 |
| ethylbenzene | (CAS-No.) 100-41-4 (EC-No.) 202-849-4 (EC Index-No.) 601-023-00-4 | 1 - 3 | Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304 |

Full text of H-statements: see section 16

| SECTION 4: First aid measures | | |
|---|--|--|
| 4.1. Description of first aid measures | | |
| First-aid measures general | : Call a poison center or a doctor if you feel unwell. | |
| First-aid measures after inhalation | : Remove person to fresh air and keep comfortable for breathing. | |
| First-aid measures after skin contact | : Wash skin with plenty of water. | |
| First-aid measures after eye contact | : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. | |
| First-aid measures after ingestion | : Call a poison center or a doctor if you feel unwell. | |
| 4.2. Most important symptoms and effe | cts, both acute and delayed | |
| Symptoms/effects | : May cause drowsiness or dizziness. | |
| Symptoms/effects after skin contact | : Repeated exposure may cause skin dryness or cracking. | |
| Symptoms/effects after eye contact | : Eye irritation. | |
| 4.3. Indication of any immediate medical attention and special treatment needed | | |
| Treat symptomatically. | | |
| SECTION 5: Firefighting measures | | |
| 5.1. Extinguishing media | | |
| Suitable extinguishing media | : Water spray. Dry powder. Foam. Carbon dioxide. | |
| 5.2. Special hazards arising from the substance or mixture | | |
| Fire hazard | : Extremely flammable aerosol. | |
| Explosion hazard | : Pressurised container: May burst if heated. | |
| Hazardous decomposition products in case of | : Toxic fumes may be released. | |

fire

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| 5.3. Advice for firefighters | |
|--|---|
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. |
| SECTION 6: Accidental release me | easures |
| 6.1. Personal precautions, protective | equipment and emergency procedures |
| 6.1.1. For non-emergency personnel | |
| Emergency procedures | : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. |
| 6.1.2. For emergency responders | |
| Protective equipment | : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". |
| 6.2. Environmental precautions | |
| Avoid release to the environment. | |
| 6.3. Methods and material for contain | ment and cleaning up |
| Methods for cleaning up | : Mechanically recover the product. |
| Other information | : Dispose of materials or solid residues at an authorized site. |
| 6.4. Reference to other sections | |
| For further information refer to section 13. | |
| SECTION 7: Handling and storage | |
| 7.1. Precautions for safe handling | |
| Precautions for safe handling | : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment. |
| Hygiene measures | : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. |
| 7.2. Conditions for safe storage, inclu | ding any incompatibilities |
| Storage conditions | : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool. |
| 7.3. Specific end use(s) | |

No additional information available

SECTION 8: Exposure controls/personal protection

| 8.1. Control parameters | | | |
|----------------------------|---------------------------------|------------------------------------|--|
| n-butyl acetate (123-86-4) | | | |
| EU | Local name | n-butyl acetate | |
| EU | Notes | (Ongoing) | |
| EU | Regulatory reference | SCOEL Recommendations | |
| ethyl acetate (141-78-6) | | | |
| EU | Local name | Ethyl acetate | |
| EU | IOELV TWA (mg/m ³) | 734 mg/m³ | |
| EU | IOELV TWA (ppm) | 200 ppm | |
| EU | IOELV STEL (mg/m ³) | 1468 mg/m ³ | |
| EU | IOELV STEL (ppm) | 400 ppm | |
| EU | Regulatory reference | COMMISSION DIRECTIVE (EU) 2017/164 | |
| butanone (78-93-3) | | | |
| EU | Local name | Butanone | |
| EU | IOELV TWA (mg/m ³) | 600 mg/m³ | |
| EU | IOELV TWA (ppm) | 200 ppm | |
| EU | IOELV STEL (mg/m ³) | 900 mg/m ³ | |
| EU | IOELV STEL (ppm) | 300 ppm | |
| EU | Regulatory reference | COMMISSION DIRECTIVE 2000/39/EC | |
| xylene (1330-20-7) | | | |
| EU | Local name | Xylene, mixed isomers, pure | |
| EU | IOELV TWA (mg/m ³) | 221 mg/m ³ | |
| EU | IOELV TWA (ppm) | 50 ppm | |
| 28/05/2018 | EN (English) | 3/9 | |

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| xylene (1330-20-7) | | |
|----------------------------|---------------------------------|---------------------------------|
| EU | IOELV STEL (mg/m ³) | 442 mg/m ³ |
| EU | IOELV STEL (ppm) | 100 ppm |
| EU | Notes | Skin |
| EU | Regulatory reference | COMMISSION DIRECTIVE 2000/39/EC |
| ethylbenzene (100-41-4) | | |
| EU | Local name | Ethylbenzene |
| EU | IOELV TWA (mg/m ³) | 442 mg/m³ |
| EU | IOELV TWA (ppm) | 100 ppm |
| EU | IOELV STEL (mg/m ³) | 884 mg/m³ |
| EU | IOELV STEL (ppm) | 200 ppm |
| EU | Notes | Skin |
| EU | Regulatory reference | COMMISSION DIRECTIVE 2000/39/EC |
| Titaniumoxide (13463-67-7) | | |
| EU | Local name | Titanium dioxide |
| EU | Notes | (Ongoing) |
| EU | Regulatory reference | SCOEL Recommendations |

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Hand protection:

Butyl rubber gloves (EN 374)

Eye protection:

eye protection (EN166)

Respiratory protection:

If vapour is released : Disposable half mask

Personal protective equipment symbol(s):



Environmental exposure controls:

Avoid release to the environment.

| SECTION 9: Physical and chemical properties | | |
|--|--------------------------------|--|
| 9.1. Information on basic physical and chemical properties | | |
| Physical state | : Liquid | |
| Colour | : Various. | |
| Odour | : No data available | |
| Odour threshold | : No data available | |
| pH | : No data available | |
| Relative evaporation rate (butylacetate=1) | : No data available | |
| Melting point | : Not applicable | |
| Freezing point | : No data available | |
| Boiling point | : < 0 °C Aerosol jet | |
| Flash point | : <-60 °C Aerosol jet | |
| Auto-ignition temperature | : No data available | |
| Decomposition temperature | : No data available | |
| Flammability (solid, gas) | : Extremely flammable aerosol. | |
| Vapour pressure | : No data available | |
| Relative vapour density at 20 °C | : No data available | |
| Relative density | : No data available | |
| | | |

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| : No data available |
|---|
| : No data available |
| : No data available |
| : No data available |
| : Pressurised container: May burst if heated. |
| : No data available |
| : No data available |
| |
| : 18 wt% |
| : 82 wt% |
| : 620 g/l |
| |

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

| SECTION 11: Toxicological information | | |
|---|------------------|--|
| 11.1. Information on toxicological effect | ts | |
| Acute toxicity (oral) | : Not classified | |
| Acute toxicity (dermal) | : Not classified | |
| Acute toxicity (inhalation) | : Not classified | |
| n-butyl acetate (123-86-4) | | |
| LD50 oral | 10760 | |
| LD50 dermal | > 14112 | |
| LC50 inhalation rat (mg/l) | 23,4 | |
| ethyl acetate (141-78-6) | | |
| LD50 oral rat | 4100 mg/kg | |
| LD50 dermal rabbit | 20000 mg/kg | |
| LD50 dermal | > | |
| LC50 inhalation rat (mg/l) | > 44 g/m³ | |
| LC50 inhalation rat (Vapours - mg/l/4h) | 22,5 mg/l/4h | |
| butanone (78-93-3) | | |
| LD50 oral | >0 | |
| LD50 dermal rat | 4000 mg/kg | |
| LD50 dermal rabbit | 6400 mg/kg | |
| LD50 dermal | > 5000 | |
| LC50 inhalation rat (mg/l) | 23,5 | |
| xylene (1330-20-7) | | |
| LD50 oral | 3523 mg/kg | |
| LD50 dermal rabbit | 12126 mg/kg | |
| LD50 dermal | 1100 mg/kg | |
| LC50 inhalation rat (mg/l) | 27,124 mg/l/4h | |
| LC50 inhalation rat (Vapours - mg/l/4h) | 27,12 mg/l/4h | |
| ethylbenzene (100-41-4) | | |
| LD50 oral | 3500 | |
| 28/05/2018 | EN (Epolish) 5/0 | |

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| ethylbenzene (100-41-4) | |
|--------------------------------------|---|
| LC50 inhalation rat (mg/l) | 17,2 |
| Titaniumoxide (13463-67-7) | |
| LD50 oral | > 10000 mg/kg |
| LD50 dermal | > 10000 mg/kg |
| LC50 inhalation rat (mg/l) | > 6,8 mg/l/4h |
| Skin corrosion/irritation | : Not classified |
| Serious eye damage/irritation | : Causes serious eye irritation. |
| Respiratory or skin sensitisation | : Not classified |
| Germ cell mutagenicity | : Not classified |
| Carcinogenicity | : Not classified |
| Reproductive toxicity | : Not classified |
| STOT-single exposure | : May cause drowsiness or dizziness. |
| xylene (1330-20-7) | |
| NOAEL (oral, rat) | 250 mg/kg bodyweight |
| STOT-repeated exposure | : Not classified |
| Aspiration hazard | : Not classified |
| TECH WHITE HOUSEHOLD RAL 9016 | |
| Vaporizer | Aerosol |
| SECTION 12: Ecological inform | ation |
| I2.1. Toxicity | |
| Ecology - general | : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. |
| Acute aquatic toxicity | : Not classified |
| Chronic aquatic toxicity | : Not classified |
| butanone (78-93-3) | |
| LC50 fish 1 | 3220 mg/l |
| EC50 Daphnia 1 | 5091 mg/l |
| xvlene (1330-20-7) | |

| E000 Bapillia | | | |
|-------------------------------------|----------------------------|-------------|--|
| xylene (1330-20 | xylene (1330-20-7) | | |
| EC50 other aqua | atic organisms 1 | > 3,4 mg/l | |
| Titaniumoxide | Titaniumoxide (13463-67-7) | | |
| LC50 fish 1 | | > 1000 mg/l | |
| | | | |
| 12.2. Persist | ence and degradability | | |
| No additional information available | | | |
| 12.3. Bioacc | umulative potential | | |
| 12.3. Divacu | unulative potential | | |

No additional information available

| 12.4. | Mobility in soil | | | |
|-------------------------------------|------------------------------------|--|--|--|
| No additional information available | | | | |
| 12.5. | Results of PBT and vPvB assessment | | | |
| No additi | ional information available | | | |

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations 13.1. Waste treatment methods Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| SECTION 14: Transport information | | | | | | |
|--|---|------------------------------------|--|--|--|--|
| In accordance with ADR / RID / IMDG / IATA / ADN | | | | | | |
| ADR | IMDG | ΙΑΤΑ | | | | |
| 14.1. UN number | | | | | | |
| 1950 | 1950 | 1950 | | | | |
| 14.2. UN proper shipping name | | | | | | |
| AEROSOLS | AEROSOLS | Aerosols, flammable | | | | |
| Transport document description | | | | | | |
| UN 1950 AEROSOLS, 2.1, (D) | UN 1950 AEROSOLS, 2.1 | UN 1950 Aerosols, flammable, 2.1 | | | | |
| 14.3. Transport hazard class(es) | | | | | | |
| 2.1 | 2.1 | 2.1 | | | | |
| | | | | | | |
| 14.4. Packing group | - | | | | | |
| Not applicable | Not applicable | Not applicable | | | | |
| 14.5. Environmental hazards | | | | | | |
| Dangerous for the environment : No | Dangerous for the environment : No Marine pollutant : No | Dangerous for the environment : No | | | | |
| No supplementary information available | | | | | | |

14.6. Special precautions for user

| - Overland transport | |
|--|------------------------------------|
| Classification code (ADR) | : 5F |
| Special provisions (ADR) | : 190, 327, 344, 625 |
| Limited quantities (ADR) | : 11 |
| Excepted quantities (ADR) | : E0 |
| Packing instructions (ADR) | : P207 |
| Special packing provisions (ADR) | : PP87, RR6, L2 |
| Mixed packing provisions (ADR) | : MP9 |
| Transport category (ADR) | : 2 |
| Special provisions for carriage - Packages (ADR) | : V14 |
| Special provisions for carriage - Loading, unloading and handling (ADR) | : CV9, CV12 |
| Special provisions for carriage - Operation (ADR) | : S2 |
| Tunnel restriction code (ADR) | : D |
| - Transport by sea | |
| Special provisions (IMDG) | : 63, 190, 277, 327, 344, 381, 959 |
| Packing instructions (IMDG) | : P207, LP200 |
| Special packing provisions (IMDG) | : PP87, L2 |
| EmS-No. (Fire) | : F-D |
| EmS-No. (Spillage) | : S-U |
| Stowage category (IMDG) | : None |
| Stowage and handling (IMDG) | : SW1, SW22 |
| Segregation (IMDG) | : SG69 |
| - Air transport | |
| PCA Excepted quantities (IATA) | : E0 |
| PCA Limited quantities (IATA) | : Y203 |
| PCA limited quantity max net quantity (IATA) | : 30kgG |
| PCA packing instructions (IATA) | : 203 |
| PCA max net quantity (IATA) | : 75kg |
| CAO packing instructions (IATA) | : 203 |
| CAO max net quantity (IATA) | : 150kg |
| Special provisions (IATA) | : A145, A167, A802 |
| 28/05/2018 | EN (English) |

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| ERG code (IATA) : 10L | | | |
|--|--|--|--|
| 14.7. Transport in bulk according to Annex II of Marpol and the IB | C Code | | |
| Not applicable | | | |
| SECTION 15: Regulatory information | | | |
| 15.1. Safety, health and environmental regulations/legislation spe | cific for the substance or mixture | | |
| 15.1.1. EU-Regulations | | | |
| The following restrictions are applicable according to Annex XVII of the RE. | ACH Regulation (EC) No 1907/2006: | | |
| 3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008 | | | |
| 3(a) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F | TECH WHITE HOUSEHOLD RAL 9016 - n-butyl acetate - ethyl acetate - butanone - xylene - ethylbenzene | | |
| 3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10 | TECH WHITE HOUSEHOLD RAL 9016 - ethyl acetate - butanone - xylene - ethylbenzene | | |
| 40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not. | n-butyl acetate - ethyl acetate - butanone - xylene - ethylbenzene | | |

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 82 wt%

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830.

Full text of H- and EUH-statements:

| Acute toxicity (dermal), Category 4 |
|--|
| Acute toxicity (inhal.), Category 4 |
| Aspiration hazard, Category 1 |
| Serious eye damage/eye irritation, Category 2 |
| Flammable liquids, Category 2 |
| Flammable liquids, Category 3 |
| Skin corrosion/irritation, Category 2 |
| Specific target organ toxicity — Repeated exposure, Category 2 |
| Specific target organ toxicity — Single exposure, Category 3, Narcosis |
| Extremely flammable aerosol. |
| Highly flammable liquid and vapour. |
| Flammable liquid and vapour. |
| Pressurised container: May burst if heated. |
| May be fatal if swallowed and enters airways. |
| Harmful in contact with skin. |
| Causes skin irritation. |
| Causes serious eye irritation. |
| |

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| H332 | Harmful if inhaled. |
|--------|--|
| H336 | May cause drowsiness or dizziness. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product