



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

ARC GLAZING & CONSTRUCTION SILICONE WHITE
Supercedes Date: 24-May-2024

Revision date 24-May-2024
Revision Number 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name ARC GLAZING & CONSTRUCTION SILICONE WHITE

Form This substance/ mixture contains nanoforms

Other means of identification

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Benelux B.V.
Denariusstraat 11
4903 RC Oosterhout
The Netherlands
Tel: + 31 162 491 000

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Ireland **NPIC - National Poison Information Centre**
Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week)
Healthcare Professionals: +353 (01) 8092566 (24 hour service)

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

Europe 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to
Regulation (EC) No. 1272/2008
[CLP]

Chronic aquatic toxicity	Category 3 - (H412)
---------------------------------	---------------------

2.2. Label elements

Hazard statements

H412 - Harmful to aquatic life with long lasting effects

EU Specific Hazard Statements

EUH208 - Contains 3-aminopropyltriethoxysilane & 2-octyl-2H-isothiazol-3-one [OIT]. May produce an allergic reaction

Precautionary Statements - EU (§28, 1272/2008)

SAFETY DATA SHEET

ARC GLAZING & CONSTRUCTION SILICONE WHITE
 Supercedes Date: 24-May-2024

Revision date 24-May-2024
 Revision Number 1

P273 - Avoid release to the environment
 P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing. Small amounts of 2-Pentanone oxime (CAS 623-40-5) are formed by hydrolysis and released upon curing. Harmful to aquatic life.

PBT & vPvB

This mixture contains substances considered to be persistent, bio-accumulating and toxic (PBT). This mixture contains substances considered to be very persistent and very bioaccumulating (vPvB).

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No..	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Silica, amorphous 5 - <10 %	231-545-4	7631-86-9	[B]	-	-	-	01-2119379499-16-XXXX
2-Pentandione, O,O',O''-(methylsilylidyne)trioxime 1 - <2.5 %	484-460-1	37859-55-5	Acute Tox. 4 (H302) Eye Irrit. 2 (H319)	-	-	-	01-2120004323-76-XXXX
Titanium dioxide 0.1- <1 %	236-675-5 (022-006-00-2)	13463-67-7	[C]	-	-	-	01-2119489379-17-XXXX
3-aminopropyltriethoxysilane 0.1 - <0.5 %	213-048-4 (612-108-00-0)	919-30-2	Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Acute Tox. 4 (H302)	-	-	-	01-2119480479-24-XXXX
Octamethylcyclotetrasiloxane [D4] 0.05 - <0.1 %	209-136-7 (014-018-00-1)	556-67-2	Repr. 2 (H361f) Aquatic Chronic 1 (H410) Flam. Liq. 3 (H226) [G]	-	-	10	01-2119529238-36-XXXX
2-octyl-2H-isothiazol-3-one [OIT] 0.0025 - <0.01 %	247-761-7 (613-112-00-5)	26530-20-1	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 2 (H330) Skin Corr. 1B (H314) Eye Dam 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	Skin Sens. 1A :: C>=0.0015%	100	100	-

Air contaminants formed when using the substance or mixture as intended

Chemical name	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
2-Pentanone oxime	484-470-6	Acute Tox. 4	-	-	-	01-2119980079-

SAFETY DATA SHEET

ARC GLAZING & CONSTRUCTION SILICONE WHITE
 Supersedes Date: 24-May-2024

Revision date 24-May-2024
 Revision Number 1

623-40-5		(H302) Eye Irrit. 2 (H319) STOT RE 2 (H373) Aquatic Chronic 3 (H412)				27-XXXX
Ethanol 64-17-5	200-578-6 (603-002-00-5)	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319)	-	-	-	01-2119457610- 43-XXXX
Methyl alcohol 67-56-1	200-659-6 (603-001-00-X)	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	STOT SE 1 :: C>=10% STOT SE 2 :: 3%<=C<10%	-	-	01-2119433307- 44-XXXX

Full text of H- and EUH-phrases: see section 16

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[B] - Substance with a Community workplace exposure limit

[C] - Components with occupational exposure limits and/or biological occupational exposure limits requiring monitoring

[G] - PBT / vPvB substance

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Silica, amorphous	231-545-4	7631-86-9	-	-	-	-	-
2-Pentandione, O,O',O''-(methylsilylidine)trioxime	484-460-1	37859-55-5	1234	-	-	-	-
Titanium dioxide	236-675-5 (022-006-00-2)	13463-67-7	-	-	-	-	-
3-aminopropyltriethoxy silane	213-048-4 (612-108-00-0)	919-30-2	1490	-	-	-	-
Octamethylcyclotetrasiloxane [D4]	209-136-7 (014-018-00-1)	556-67-2	-	-	-	-	-
2-octyl-2H-isothiazol-3-one [OIT]	247-761-7 (613-112-00-5)	26530-20-1	125+	311+	0.27+	0.27+	0.27+

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Notes

See section 16 for more information

SAFETY DATA SHEET

ARC GLAZING & CONSTRUCTION SILICONE WHITE
Supercedes Date: 24-May-2024

Revision date 24-May-2024
Revision Number 1

Chemical name	Notes
Titanium dioxide - 13463-67-7	V,W,10

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.
Inhalation	Remove to fresh air. If symptoms persist, call a doctor.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	None known.
Effects of Exposure	No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released, when the product is exposed to moisture or water. Treat symptomatically.
------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Water spray, carbon dioxide (CO ₂), dry chemical, alcohol-resistant foam.
Unsuitable extinguishing media	Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Thermal decomposition can lead to release of irritating gases and vapours.
Hazardous combustion products	Carbon oxides. Carbon dioxide (CO ₂). Silicon dioxide. Thermal decomposition can lead to release of irritating and toxic gases and vapours.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters	Wear self contained breathing apparatus for fire fighting if necessary.
---	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

SAFETY DATA SHEET

ARC GLAZING & CONSTRUCTION SILICONE WHITE
Supercedes Date: 24-May-2024

Revision date 24-May-2024
Revision Number 1

Personal precautions Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Ensure adequate ventilation.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Do not scatter spilled material with high pressure water streams.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation.

General hygiene considerations Take off all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Keep away from food, drink and animal feedingstuffs. Protect from moisture.

Recommended storage temperature Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s)
Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product This product contains substances which in their raw state are powder form, however in this product they are in a non-respirable form. Inhalation of powder/dust particles is unlikely to occur from exposure to this product

Chemical name	European Union	Ireland	United Kingdom
Limestone 1317-65-3	-	TWA: 10 mg/m ³ TWA: 4 mg/m ³	TWA: 10 mg/m ³ TWA: 4 mg/m ³

SAFETY DATA SHEET

ARC GLAZING & CONSTRUCTION SILICONE WHITE
Supersedes Date: 24-May-2024

Revision date 24-May-2024
Revision Number 1

		STEL: 30 mg/m ³ STEL: 12 mg/m ³	STEL: 30 mg/m ³ STEL: 12 mg/m ³
Silica, amorphous 7631-86-9	-	TWA: 6 mg/m ³ TWA: 2.4 mg/m ³ STEL: 18 mg/m ³ STEL: 7.2 mg/m ³	TWA: 6 mg/m ³ TWA: 2.4 mg/m ³ STEL: 18 mg/m ³ STEL: 7.2 mg/m ³
Ethanol 64-17-5	-	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1920 mg/m ³ STEL: 3000 ppm STEL: 5760 mg/m ³
Methyl alcohol 67-56-1	TWA: 200 ppm TWA: 260 mg/m ³ *	TWA: 200 ppm TWA: 260 mg/m ³ STEL: 600 ppm STEL: 780 mg/m ³ Sk*	TWA: 200 ppm TWA: 266 mg/m ³ STEL: 250 ppm STEL: 333 mg/m ³ Sk*
Titanium dioxide 13463-67-7	-	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m ³	

3-aminopropyltriethoxysilane (919-30-2)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	59 mg/m ³	
worker Short term Systemic health effects	Inhalation	59 mg/m ³	
worker Long term Systemic health effects	Dermal	8.3 mg/kg bw/d	
worker Short term Systemic health effects	Dermal	8.3 mg/kg bw/d	

Octamethylcyclotetrasiloxane [D4] (556-67-2)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	73 mg/m ³	

Derived No Effect Level (DNEL)			
Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	

SAFETY DATA SHEET

ARC GLAZING & CONSTRUCTION SILICONE WHITE
 Supersedes Date: 24-May-2024

Revision date 24-May-2024
 Revision Number 1

3-aminopropyltriethoxysilane (919-30-2)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	17 mg/m ³	
Consumer Short term Systemic health effects	Inhalation	17.4 mg/m ³	
Consumer Long term Systemic health effects	Dermal	5 mg/kg bw/d	
Consumer Short term Systemic health effects	Dermal	5 mg/kg bw/d	

Octamethylcyclotetrasiloxane [D4] (556-67-2)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	13 mg/m ³	
Consumer Long term Systemic health effects	Oral	3.7 mg/kg bw/d	

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

3-aminopropyltriethoxysilane (919-30-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.33 mg/l
Marine water	0.033 mg/l

Octamethylcyclotetrasiloxane [D4] (556-67-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.0015 mg/l
Marine water	0.00015 mg/l
Freshwater sediment	3 mg/kg
Marine sediment	0.3 mg/kg
Soil	0.54 mg/kg
Sewage treatment plant	10 mg/l

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment
Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

SAFETY DATA SHEET

ARC GLAZING & CONSTRUCTION SILICONE WHITE
Supersedes Date: 24-May-2024

Revision date 24-May-2024
Revision Number 1

Hand protection	standard EN 166 Wear suitable gloves. Recommended Use: Neoprene™. Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374
Skin and body protection	None under normal use conditions.
Respiratory protection	In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation, especially in confined areas.
Recommended filter type:	Organic gases and vapours filter conforming to EN 14387. White. Brown.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid	
Appearance	Paste	
Colour	See section 1 for more information	
Odour	Characteristic.	
Property	Values	Remarks • Method
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	No data available	None known
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	No data available	Not applicable. Insoluble in water.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	> 21 mm ² /s	
Dynamic viscosity	No data available	
Water solubility	No data available. Product cures with moisture	
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known
Bulk Density	No data available	
Liquid Density	1.26 g/cm ³	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

Solid content (%)	No information available	
VOC content		No data available

9.2.1. Information with regards to physical hazard classes
Not applicable

9.2.2. Other safety characteristics
No information available

SAFETY DATA SHEET

ARC GLAZING & CONSTRUCTION SILICONE WHITE
Supersedes Date: 24-May-2024

Revision date 24-May-2024
Revision Number 1

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Incompatible materials Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact May cause sensitisation in susceptible persons.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity

Numerical measures of toxicity

SAFETY DATA SHEET

ARC GLAZING & CONSTRUCTION SILICONE WHITE
 Supercedes Date: 24-May-2024

Revision date 24-May-2024
 Revision Number 1

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	53,572.10 mg/kg
ATEmix (dermal)	86,870.20 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/l
ATEmix (inhalation-vapour)	>20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Silica, amorphous	=7900 mg/kg (Rattus)	> 5000 mg/kg (Oryctolagus cuniculus)	>2.2 mg/L (Rattus) 1 h
2-Pentandione, O,O',O''-(methylsilylidine)trioxime	LD50 =1234 mg/kg bw (Rattus)(OECD guideline 425)	LD50 > 2000 mg/kg (Rattus) EU Method B.3	-
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L (Rattus) 4 h
3-aminopropyltriethoxysilane	LD50 = 1490 mg/kg (Rattus, female) EPA OTS 798.1175 LD50 = 2690 mg/kg (Rattus, male) EPA OTS 798.1175	LD50 = 4076 mg/kg (Oryctolagus cuniculus) EPA OTS 798.1100	LC50 >144 mg/L (6h) Rattus (Vapour)
Octamethylcyclotetrasiloxane [D4]	LD50 > 4800 mg/kg (Rattus) OECD 401	LD50 > 2400 mg/kg (Rattus) OECD 402	=36 g/m ³ (Rattus) 4 h
2-octyl-2H-isothiazol-3-one [OIT]	=125 mg/kg (Rattus)	= 690 mg/kg (Oryctolagus cuniculus)	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Eye			Non-irritant

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

Respiratory or skin sensitisation

No classification is proposed, based on conclusive negative data. OECD Test No. 406: Skin Sensitisation. No sensitisation responses were observed. May cause sensitisation in susceptible persons.

Product Information			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	No sensitisation responses were observed

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

ARC GLAZING & CONSTRUCTION SILICONE WHITE
 Supersedes Date: 24-May-2024

Revision date 24-May-2024
 Revision Number 1

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	European Union
Titanium dioxide	Carc. 2

Reproductive toxicity Based on available data, the classification criteria are not met.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical name	European Union
Octamethylcyclotetrasiloxane [D4]	Repr. 2

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Silica, amorphous 7631-86-9	EC50: =440mg/L (72h, Pseudokirchneriella subcapitata)	LC50: =5000mg/L (96h, Brachydanio rerio)	-	EC50: =7600mg/L (48h, Ceriodaphnia dubia)		
2-Pentandione, O,O',O''-(methylsilylidyne)trioxime 37859-55-5	EC50 (72h) = 88 mg/L (Pseudokirchneriella subcapitata) OECD 201	LC50 (96h) >113 mg/L (Oncorhynchus mykiss) Static (OECD Guideline 203)	-	EC50 (48h) >100 mg/L (Daphnia magna) static (OECD guideline 202)		
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
3-aminopropyltriethoxy silane 919-30-2	EC50 (72h) >1000 mg/L Green algae	LC50 (96h) >934 mg/L (Brachydanio)	-	EC50 (48h) =331 mg/L Daphnia magna (OECD		

SAFETY DATA SHEET

ARC GLAZING & CONSTRUCTION SILICONE WHITE
 Supersedes Date: 24-May-2024

Revision date 24-May-2024
 Revision Number 1

	(desmodesmus subspicatus) (OECD TG 201)	rerio) (OECD TG 203)		TG 202)		
Octamethylcyclotetrasiloxane [D4] 556-67-2	-	LC50: >1000mg/L (96h, Lepomis macrochirus) LC50: >500mg/L (96h, Brachydanio rerio)	-	EC50: =25.2mg/L (24h, Daphnia magna)		10
2-octyl-2H-isothiazol-3-one [OIT] 26530-20-1	EC50(72h) = 0.084 mg/L (Scenedesmus subspicatus) (OECD 201)	LC50 (96h) = 0.036 mg/L (Oncorhynchus mykiss) (OECD 203)	-	EC50 (48h) =0.42 mg/L (OECD 202)	100	100

12.2. Persistence and degradability

Persistence and degradability No information available.

Silica, amorphous (7631-86-9)

Method	Exposure time	Value	Results
			The methods for determining biodegradability are not applicable to inorganic substances

Octamethylcyclotetrasiloxane [D4] (556-67-2)
 2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

Method	Exposure time	Value	Results
OECD Test No. 309: Aerobic Mineralization in Surface Water - Simulation Biodegradation Test		Half-life 0.6-1.4 d	Readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
2-Pentandione, O,O',O''-(methylsilyldi)trioxime	1.25
3-aminopropyltriethoxysilane	1.7
Octamethylcyclotetrasiloxane [D4]	6.49
2-octyl-2H-isothiazol-3-one [OIT]	2.92

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product contains substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Silica, amorphous	The substance is not PBT / vPvB
2-Pentandione, O,O',O''-(methylsilyldi)trioxime	The substance is not PBT / vPvB
Titanium dioxide	The substance is not PBT / vPvB
3-aminopropyltriethoxysilane	The substance is not PBT / vPvB
Octamethylcyclotetrasiloxane [D4]	PBT & vPvB
2-octyl-2H-isothiazol-3-one [OIT]	The substance is not PBT / vPvB

SAFETY DATA SHEET

ARC GLAZING & CONSTRUCTION SILICONE WHITE
Supersedes Date: 24-May-2024

Revision date 24-May-2024
Revision Number 1

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

Component Information		
Octamethylcyclotetrasiloxane [D4] (556-67-2)		
Method	Results	Species
Endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100(3) or Commission Regulation (EU) 2018/605(4).	Negative.	

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
Contaminated packaging	Handle contaminated packages in the same way as the product itself.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	-
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	None

IMDG

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP
14.6 Special precautions for user	
Special Provisions	None
14.7 Maritime transport in bulk according to IMO instruments	
Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated

SAFETY DATA SHEET

ARC GLAZING & CONSTRUCTION SILICONE WHITE
Supersedes Date: 24-May-2024

Revision date 24-May-2024
Revision Number 1

14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Biocidal Products Regulation (EU) No 528/2012 (BPR)

This product contains a biocidal product for the preservation of the dry film Contains: 2-octyl-2H-isothiazol-3-one [OIT]

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

SAFETY DATA SHEET

ARC GLAZING & CONSTRUCTION SILICONE WHITE
Supersedes Date: 24-May-2024

Revision date 24-May-2024
Revision Number 1

Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour
H301 - Toxic if swallowed
H302 - Harmful if swallowed
H311 - Toxic in contact with skin
H314 - Causes severe skin burns and eye damage
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H319 - Causes serious eye irritation
H330 - Fatal if inhaled
H361f - Suspected of damaging fertility
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects

Notes relating to the identification, classification and labelling of substances

Note V: If the substance is to be placed on the market as fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied

Note W: It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung

Notes relating to the classification and labelling of mixtures

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances

vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT RE: Specific target organ toxicity - Repeated exposure

STOT SE: Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

LOW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG: International Maritime Dangerous Goods

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
AGW	Occupational exposure limit value	BGW	Biological limit value
Ceiling	Maximum limit value	Sk*	Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	On basis of test data
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method

SAFETY DATA SHEET

ARC GLAZING & CONSTRUCTION SILICONE WHITE
Supersedes Date: 24-May-2024

Revision date 24-May-2024
Revision Number 1

Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)
European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)
European Chemicals Agency (ECHA) (ECHA_API)
Environmental Protection Agency
Acute Exposure Guideline Level(s) (AEGl(s))
International Uniform Chemical Information Database (IUCLID)
National Institute of Technology and Evaluation (NITE)
NIOSH (National Institute for Occupational Safety and Health)
Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications
Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme
Organisation for Economic Co-operation and Development Screening Information Data Set

Prepared By Product Safety & Regulatory Affairs

Revision date 24-May-2024

Training Advice No information available

Further information No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Regulation (EC) No. 1907/2006 as amended by Regulation (EU) No. 2020/878, and Regulation (EC) No. 1272/2008

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet