

Technical Data Sheet

Date of compilation: 12/07/2018

ARC CABLE TIES

DESCRIPTION

Manufactured from high grade Nylon 6.6 giving strength and flexibility.

Manufactured in lengths from 100mm up to 880mm they are suitable for many applications, servicing the electronics, heavy electrical, engineering & DIY industries.

FLAME RESISTANCE

In accordance with UL94V2

TEMPERATURE RANGE

For continuous use -40°C to +85°C

UV RESISTANCE

Black Colour is resistant to ultra violet light.
White Colour has not been tested.



TECHNICAL DATA

Length (mm)	Width (mm)	MIN LOOP
		Tensile Strength (kg)
100	2.5	8
140	3.6	18
200	4.8	22
250	4.8	22
300	4.8	22
360	4.8	22
430	4.8	22
500	4.8	22
380	7.6	55
450	9	80
550	9	80
610	9	80
710	9	80
750	9	80
880	12.4	110

Technical Data Sheet

Date of compilation: 12/07/2018

ARC CABLE TIES

NOTE

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Full information and advice is freely available from our Technical Services Department e-mail technical@arcbuildingproducts.ie. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our representatives, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.