

SAFETY DATA SHEET

POT-CEM RAPID SET CEMENT

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier Trade name POT-CEM RAPID SET CEMENT Product no. RCEM004 Unique formula identifier (UFI) HR2P-F2UM-0002-4VEG 1.2. Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture **Building & Construction Work** Uses advised against None known. 1.3. Details of the supplier of the safety data sheet Company and address **Arc Building Products** IDA Business & Technology Park, Ballynattin Y14 A370 Arklow, Co. Wicklow Ireland Phone +353 (0)402 32370 Fax +353 (0)402 24168 www.arcbuildingproducts.ie E-mail sales@arcbuildingproducts.ie Revision 05/10/2023 SDS Version 1.0 1.4. Emergency telephone number The National Poisons Information Centre (NPIC) Public: +353 (0) 1 809 2166 (7 days a week, 8am- 10pm) Healthcare professionals: +353 (0) 1 809 2566 (24 h service) See also section 4 "First aid measures" SECTION 2: Hazards identification 2.1. Classification of the substance or mixture Skin Irrit. 2; H315, Causes skin irritation.

Skin Irrit. 2; H315, Causes skin irritation. Eye Dam. 1; H318, Causes serious eye damage. STOT SE 3; H335, May cause respiratory irritation. 2.2. Label elements

Hazard pictogram(s)



Signal word Danger Hazard statement(s) Causes skin irritation. (H315) Causes serious eye damage. (H318)



May cause respiratory irritation. (H335)
Precautionary statement(s)
General
If medical advice is needed, have product container or label at hand. (P101) Keep out of reach of children. (P102)
Prevention
Wash hands and exposed skin thoroughly after handling. (P264) Wear protective gloves/protective clothing/eye protection/face protection. (P280)
Response
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338) Immediately call a POISON CENTER/doctor. (P310)
Storage Store locked up. (P405)
Disposal
Dispose of contents/container in accordance with local regulation (P501)
Hazardous substances Cement, portland, chemicals
Additional labelling
EUH203, Contains chromium (VI). May produce an allergic reaction. The content of water-soluble chromate is less than 2 ppm in dry storage up to 12 months from production date. If stored under moist conditions, chromate reduction may be impaired. UFI: HR2P-F2UM-0002-4VEG
2.3. Other hazards
Additional warnings
Upon mixing the product with water it will become corrosive. When wet concrete or mortar is trapped against the skin by falling inside a worker's boots or gloves or by soaking through protective clothing—the result may be first, second, or third degree burns. The product contains quartz; working processes in which respirable quartz dust can be developed are covered by the EU cancer Regulation.
This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.
This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.
SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Cement, portland, chemicals	CAS No.: 65997-15-1 EC No.: 266-043-4 REACH: Index No.:	25-40%	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335	[19]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.



Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Skin in contact with wet cement should be washed immediately with large amounts of cool clean water. If skin irritation occurs: Get medical advice/attention.

Eye contact

If in eyes: Flush eyes with plenty of water or salt water (20-30 °C) for at least 30 minutes and continue until irritation stops. Remove contact lenses. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Workers using cement may develop an allergy to chromium, with symptoms ranging from a mild rash to severe skin ulcers. In addition to skin reactions, hexavalent chromium can cause occupational asthma. Symptoms include wheezing and difficulty breathing. Workers may develop both skin and respiratory allergies to hexavalent chromium. The product contains substances that cause serious eye damage. Contact with these substances can cause irreversible effects on the eye / serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Sulphur oxides

Some metal oxides

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the National Poisons Information Centre (NPIC) on +353 (0) 1 809 256 (24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances. Ensure adequate ventilation, especially in confined areas. Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Collect spills carefully. Moist the material with water in order to prevent the formation and propagation of dust. Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections



See section 13 "Disposal considerations" on handling of waste. See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid direct contact with the product.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Powder trickling out onto the floor or onto other containers must be prevented. Recommended storage material

Keep only in original packaging.

Storage temperature

5 - 30 degrees Celsius

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Cement, portland, chemicals Long term exposure limit (8 hours) (mg/m³): 1 (Respirable Fraction)

Calcium Sulfate Long term exposure limit (8 hours) (mg/m³): 10

Calcium sulfate

Long term exposure limit (8 hours) (mg/m³): 10

2021 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2015) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019).

DNEL

Calcium sulfate

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Inhalation	5.29 mg/m³
Long term – Systemic effects - Workers	Inhalation	21.17 mg/m ³
Short term – Systemic effects - General population	Inhalation	3811 mg/m ³
Short term – Systemic effects - Workers	Inhalation	5082 mg/m³
Long term – Systemic effects - General population	Oral	1.52 mg/kg bw/day
Short term – Systemic effects - General population	Oral	11.4 mg/kg bw/day

Calcium Sulfate

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Inhalation	5.29 mg/m ³
Long term – Systemic effects - Workers	Inhalation	21.17 mg/m ³
Short term – Systemic effects - General population	Inhalation	3811 mg/m ³
Short term – Systemic effects - Workers	Inhalation	5082 mg/m ³
Long term – Systemic effects - General population	Oral	1.52 mg/kg bw/day
Short term – Systemic effects - General population	Oral	11.4 mg/kg bw/day



PNEC Calcium sulfate		
Route of exposure:	Duration of Exposure:	PNEC:
Sewage treatment plant		100 mg/L
Calcium Sulfate		
Route of exposure:	Duration of Exposure:	PNEC:
Sewage treatment plant		100 mg/L

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Provide adequate hygiene facilities on site for workers to wash hands and face at the end of a job and before eating, drinking, smoking, or using the toilet. Facilities for cleaning boots and changing clothes should also be available.

Clothing contaminated by wet cement should be quickly removed. Skin in contact with wet cement should be washed immediately with large amounts of cool clean water.

If possible, avoid working processes where respiratory quartz dust may be developed.

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Mix dry cement in well-ventilated areas.

Work in ways that minimize the amount of cement dust released.

In connection with work processes in which respirable quartz dust can be developed e.g. when cutting and drilling in concrete, extracted air must not be recycled according to EU Cancer Regulation.

Airborne gas and dust concentrations must be kept at a minimum and below current limit values (see above).

Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and showers are clearly marked.

Ensure that eyewash stations and safety showers are located within easy reach.

Airborne gas and dust concentrations must be kept at a minimum. Provide efficient mechanical ventilation. If not possible use suitable respiratory equipment.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Don't wash your hands with water from buckets used for cleaning tools.

Take off contaminated clothing and wash it before reuse.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment

Generally

Use only CE marked protective equipment.

Respiratory Equipment

Туре	Class	Colour	Standards	
-			EN 149	
kin protection				
Recommended	Type/Category	St	tandards	
-				R





	Material	Glove thickness (mm)	Breakthrough time (min.)	Standards		
	Nitrile					
Ev	e protection					
,	Туре	Standards				
	EN 166	EN 166				
SECT	TON 9: Physical and c	hemical properties				
Ph Co Dc De Kir Pa Phase So So Va Re	ysical state Powder lour Grey lour / Odour threshol None Testing not relevant ensity (g/cm ³) 1.6 - 2.0 nematic viscosity Does not apply to so rticle characteristics Testing not relevant e changes elting point/Freezing (Testing not relevant ftening point/range (Does not apply to so iling point (°C) Does not apply to so pour pressure	or not possible due to the lids. or not possible due to the point (°C) or not possible due to the waxes and pastes) (°C) lids. lids. or not possible due to the lids.	e nature of the product. e nature of the product. e nature of the product.			
Data		or not possible due to the	e nature of the product.			
Fla Au	Does not apply to so immability (°C) Testing not relevant to-ignition temperatu	or not possible due to the ure (°C) or not possible due to the sion limit (% v/v)				
n-(ility lubility in water Testing not relevant octanol/water coeffici	or not possible due to the				



Testing not relevant or not possible due to the nature of the product. 9.2. Other information Other physical and chemical parameters No data available. Oxidizing properties Testing not relevant or not possible due to the nature of the product.	
SECTION 10: Stability and reactivity	
 10.1. Reactivity No data available. 10.2. Chemical stability The product is stable under the conditions, noted in section 7 "Handling and storage". 10.3. Possibility of hazardous reactions None known. 10.4. Conditions to avoid None known. 10.5. Incompatible materials Strong acids, strong bases, strong oxidizing agents, and strong reducing agents. 10.6. Hazardous decomposition products The product is not degraded when used as specified in section 1. 	
SECTION 11: Toxicological information	
 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity Based on available data, the classification criteria are not met. Skin corrosion/irritation Causes skin irritation. Serious eye damage/irritation Causes serious eye damage. Respiratory sensitisation Based on available data, the classification criteria are not met. Skin sensitisation Based on available data, the classification criteria are not met. Skin sensitisation Based on available data, the classification criteria are not met. Gern cell mutagenicity Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met. Reproductive toxicity Based on available data, the classification criteria are not met. STOT-single exposure Based on available data, the classification criteria are not met. STOT-repeated exposure Based on available data, the classification criteria are not met. Aspiration hazard Based on available data, the classification criteria are not met. Aspiration hazard Based on available data, the classification criteria are not met. 11.2. Information on other hazards Long term effects The product contains substances that cause serious eye damage. Contact with these substances can cau effects on the eye / serious eye damage. Endocrine disrupting properties This mi	



SECTION 12: Ecological information

12.1. Toxicity

No data available.

- 12.2. Persistence and degradability No data available.
- 12.3. Bioaccumulative potential No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste. HP 4 - Irritant (skin irritation and eye damage) HP 5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity Dispose of contents/container to an approved waste disposal plant. Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

EWC code

Not applicable.

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / 1	14.2 ID UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

* Packing group

** Environmental hazards

Additional information

Not dangerous goods according to ADR, IATA and IMDG.

14.6. Special precautions for user

Not applicable.

- 14.7. Maritime transport in bulk according to IMO instruments
 - No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Restrictions for application

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered. Demands for specific education



No specific requirements. SEVESO - Categories / dangerous substances Not applicable. Additional information Not applicable. Sources Protection of Young Persons (Employment) Act, 1996 Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). 15.2. Chemical safety assessment No SECTION 16: Other information Full text of H-phrases as mentioned in section 3 H315, Causes skin irritation. H318, Causes serious eye damage. H335, May cause respiratory irritation. Abbreviations and acronyms ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor CAS = Chemical Abstracts Service CE = Conformité Européenne (European conformity) CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] CSA = Chemical Safety Assessment CSR = Chemical Safety Report DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EINECS = European Inventory of Existing Commercial chemical Substances ES = Exposure Scenario EUH statement = CLP-specific Hazard statement EuPCS = European Product Categorisation System EWC = European Waste Catalogue GHS = Globally Harmonized System of Classification and Labelling of Chemicals IARC = International Agency for Research on Cancer (IARC) IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) OECD = Organisation for Economic Co-operation and Development PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail RRN = REACH Registration Number SCL = A specific concentration limit SVHC = Substances of Very High Concern STOT-RE = Specific Target Organ Toxicity - Repeated Exposure STOT-SE = Specific Target Organ Toxicity - Single Exposure TWA = Time weighted average UN = United Nations UVBC = Unknown or variable composition, complex reaction products or of biological materials VOC = Volatile Organic Compound vPvB = Very Persistent and Very Bioaccumulative Additional information The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by



Regulation (EC) No. 1272/2008 (CLP). The safety data sheet is validated by Technical

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: IE-en