

Technical Data Sheet

Date of compilation: 04/08/2021

ARC WOOD FILLER

DESCRIPTION

Arc Wood Filler is a pre-coloured one part high strength polyester wood filler supplied in a handy 250ml pack size.

Used for the filling and repair of small pinholes and cracks below 5mm depth. Particularly suited to flat face-up applications and for materials such as MDF and chipboard. Fast drying in the normal atmosphere.



KEY BENEFITS

- Easy to sand down to perfection.
- Ideal for interior use - very low odour.
- Handy pack size in a range of suitable colour matches.
- Easy to work with, particularly for large flat surfaces.
- Accepts all finishes including all known paint systems and varnishes.
- Strong plastic screw lid packaging with heat seal foil freshness closure.

PREPARATION

Prior to application, all surfaces should be clean, dry, sound and free from oil or grease. On old timber, any rotten or weak areas should be cut back to solid timber. Smooth areas should be slightly abraded to ensure a good key is obtained.

MIXING

This product can be used straight from the container without any mixing. After a long period of storage, a small amount of liquid may form on the surface of the material, this can easily be remixed into the material with a small amount of stirring without any loss of performance.

APPLICATION

Apply the product using a putty knife or spatula direct to the area of timber to be repaired. Shape the product as required with a spreader or flat former. Leave enough excess proud of the surface to allow for sanding. Allow to cure before finishing. It is important that the total surface of the repair is fully sanded to ensure that the stain or finish can fully penetrate. Certain timbers are highly absorbent which may result in the filler being more noticeable. It is recommended that trials are conducted on an inconspicuous area prior to full scale production to ensure suitability. Gelling time is around 30 min at 15°C and is to full strength after 2 hours. The product should not be used below -5°C.

Technical Data Sheet

Date of compilation: 04/08/2021

ARC WOOD FILLER

STORAGE

Shelf life is 12 months from manufacture date when stored in original unopened containers between +5° C and +25° C.

PRESENTATION

Colours: Pine, Light Oak, White, Mahogany and Teak.
Tubes: 250ml. Box: 6 units.

HEALTH & SAFETY

See Health & Safety data sheet before using the product.

NOTE

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Full information and advice is freely available from our Technical Services Department e-mail technical@arcbuildingproducts.ie. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our representatives, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.